



RMCARD303 Remote Management Card

Remotely manage, monitor and control your UPS from a web browser or SNMP management application.

The CyberPower RMCARD303 is a full-featured network UPS management device that remotely manages, monitors, and controls CyberPower UPS products.

The internal card allows remote monitoring and control of a UPS via Web Browser or NMS connection. By utilizing the auto-shutdown software, servers and workstations stay protected from data loss due to power failure. An optional Environmental Sensor (ENVIROSENSOR) can be added to monitor a server room / datacenter's temperature and humidity. Event logging tracks the UPS operational history. Automated event notifications via email, SMS text, or SNMP Trap can be setup to insure real time status of changes to the UPS and its input voltages. Firmware can be updated by users to insure they have the latest features and updates.

MD5 security management is also provided to protect the integrity of the UPS and network.

A Three-Year Warranty ensures that this network management card has passed our highest quality standards in design, assembly, material and workmanship.

Features

- Real time UPS monitoring
- Support for optional environment sensor management
- Remote management and configuration of UPS (HTTP) via Web Browser or NMS
- Automatic events notification via Email, SMS, and SNMP Trap
- User upgradeable firmware
- Event and Data Logging
- Support TCP/IP, UDP, SNMP/HTTP, SNMPv3, IPv6, NTP, SMTP protocols
- MD5 security management

RMCARD303 Remote Management Card

Remotely manage, monitor and control your UPS from a web browser or SNMP management application.

GENERAL	
Type	Network Management Card
COMMUNICATION	
Protocols	HW2.0 supports - TCP/IP, UDP, SNMP V1/V3, Http/Https, NTP, Telnet, DNS, SMTP, IPv4/v6 protocols HW1.0 supports - TCP/IP, UDP, SNMP V1, HTTP, NTP, Telnet, DNS, SMTP, IPv4 protocols
Network Connection	RJ45 - 10/100Mbps Ethernet
PHYSICAL	
Dimensions (WxHxD) (in.)	2.64 x 1.65 x 5.28
Dimensions (WxHxD) (mm.)	67.06 x 41.91 x 134.11
Weight (lbs.)	0.13
Weight (kg.)	0.06
SHIPPING DIMENSIONS	
Dimensions (WxHxD) (in.)	6.50 x 2.40 x 6.80
Dimensions (WxHxD) (mm.)	165 x 61 x 173
Weight (lbs.)	0.42
Weight (kg.)	0.19
ENVIRONMENTAL	
Operating Temperature	32°F to 104°F / 0°C to 40°C
Operating Humidity	0% - 90% non-condensing
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	14°F to 122°F / -10°C to 50°C
Storage Relative Humidity	0% - 95% non condensing
Storage Elevation	0-50000 feet (0-15000 meters)
COMPATIBILITY	
UPS Models	*Online Series UPS with Smart Slot
CERTIFICATIONS	
Safety	FCC Class A, CE
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited